



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : B32B 27/20, B65D 65/20	A1	(11) International Publication Number: WO 99/61245 (43) International Publication Date: 2 December 1999 (02.12.99)
(21) International Application Number: PCT/SE99/00843 (22) International Filing Date: 18 May 1999 (18.05.99) (30) Priority Data: 9801809-6 22 May 1998 (22.05.98) SE (71) Applicant (for all designated States except US): TETRA LAVAL HOLDINGS & FINANCE S.A. [SE/SE]; Avenue Général-Guisan 70, CH-1009 Pully (SE). (72) Inventors; and (75) Inventors/Applicants (for US only): BERGHOLTZ, Lars [SE/SE]; Rapsvägen 38, S-263 54 Höganäs (SE). KLINT, Lotta [SE/SE]; Klockaregatan 2b, S-252 49 Helsingborg (SE). (74) Agent: SUNDELL, Håkan; AB Tetra Pak, Patent Dept., Ruben Rausing's gata, S-221 86 Lund (SE).		(81) Designated States: AE, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZA, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SL, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: A PACKAGING MATERIAL AND PACKAGES PRODUCED FROM THE MATERIAL FOR LIGHT-SENSITIVE PRODUCTS <div data-bbox="329 1199 1308 1602" data-label="Image"> <p>The diagram shows a cross-section of a packaging material (10). It consists of three distinct layers. The top layer is labeled 12, the middle layer is labeled 11, and the bottom layer is labeled 13. The middle layer (11) is filled with numerous small, dark, irregular shapes representing carbon black particles. Three specific particles are labeled 11a, 11b, and 11c. The entire structure is indicated by a bracket and the label 10.</p> </div> (57) Abstract <p>The disclosure relates to a packaging material and packages, for example bottles, produced from the packaging material, for light-sensitive products. The packaging material (10) includes at least one layer (11) of mineral-filled plastic which, for light barrier elevating purposes, also includes particles (11c) of carbon black. The material (10) which is preferably of triple-layer type, has the mineral-filled layer (11) containing carbon black disposed between outer, surrounding layers (12 and 13) of plastic which is preferably the same plastic as the plastic in the interjacent layer (11). In order to conceal the interjacent layer (11) containing carbon black, at least one, but preferably both, of the outer plastic layers may incorporate white pigment or other white colouring agent, preferably titanium dioxide (TiO₂). Bottles are produced from the packaging material (10) by a combined extrusion and blow moulding operation in a per se known manner using conventional process equipment.</p>		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A PACKAGING MATERIAL AND PACKAGES PRODUCED FROM THE MATERIAL FOR LIGHT-SENSITIVE PRODUCTS

TECHNICAL FIELD

5 The present invention relates to a packaging material including layers of plastic permanently united with one another and of which at least one layer includes, for the purpose of elevating light-barrier properties, distributed particles of carbon black. The present invention also relates to a package produced from the packaging material for light-sensitive products.

10

BACKGROUND ART

Both packaging material and packages of the type described above are known in the art. For example, there occur on the market bottles which are produced by a combined extrusion/blow moulding operation of such triple-layer material. The material in these bottles has an interjacent layer of HDPE with admixed particles of carbon black and outer layers of HDPE on both sides of the interjacent layer.

15 The prior art bottles are employed, int. al. for transporting so-called UHT milk, i.e. milk which, for the purpose of extending its shelf life, has been subjected to a heat treatment at approx. 135-150°C during approx. 1-2 seconds for reducing or eliminating the number of harmful micro-organisms occurring in the milk.

20 Since milk is a very light-sensitive product which does not stand lengthy exposure to light, in particular within the ultra violet wavelength range without being damaged, it is important that the milk is stored in its package in such a manner that it is not unnecessarily exposed to ultra violet radiation from its ambient surroundings.

25 Plastic layers consisting exclusively of HDPE are almost totally devoid of barrier properties against light, in particular ultra violet light, and consequently do not alone afford the light protection which is necessary in order for the milk to be able to be stored with the desired extended shelf life. In order to make the long-term storage of milk possible in the prior art bottles, particles of a light-absorbing material, normally carbon black, are therefore incorporated in the interjacent layer of the packaging material, such particles efficiently absorbing, and thereby preventing impinging light

30

35

from the outer ambient surroundings of the bottle from penetrating through the wall material of the bottle and reaching the packed milk.

However, particles of carbon black in the large quantities that are employed in the prior art packaging material make the interjacent layer extremely blackened, which could readily be seen through the outer HDPE layers of the bottle and give the bottle an unappealing black appearance if the interjacent layer were not concealed. In order to conceal the thus blackened interjacent layer, the outer HDPE layers of the bottle are therefore provided with a white colouring pigment of titanium dioxide, TiO_2 , in a sufficient quantity to conceal the black interjacent layer beneath and thereby impart to the bottle a more consumer-attractive white appearance.

However, the problem inherent in the prior art triple-layer material is that, as was mentioned above, it requires relatively large quantities of the blackening particles of carbon black in the interjacent layer in order to attain the requisite light barrier properties, at the same time as it also requires correspondingly large quantities of white pigment (TiO_2) in the outer layer for concealing the undesirable blackening caused by the particles. This entails unnecessary, but unavoidable, increased material consumption and thereby increased material costs for producing the material.

Another drawback which is related to the unnecessarily large quantity of carbon black particles is that the waste material which occurs in the bottle producing process cannot directly be recycled into the process because of the extreme blackening, but must first be whitened by the addition of white pigment (TiO_2) or other white colouring matter in order to be able to be recycled and reused in the process. Such a handling involves extra material consumption and increased material costs, which often renders recycling and reuse unprofitable.

OBJECT OF THE INVENTION

The task forming the basis of the present invention is therefore to provide a packaging material of the type described by way of introduction which neither requires large quantities of carbon black to achieve superior light barrier properties nor large quantities of white pigment (TiO_2) or other white colouring matter in order to impart to the packaging material a white appearance.

SOLUTION

This task is solved according to the present invention by means of a packaging material possessing the characterizing feature as set forth in appended Claim 1. Improvements and expedient embodiments of the present invention have further been given the characterizing features as set forth in the appended subclaims.

SUMMARY OF THE INVENTION

The present invention is the result of the surprising discovery that a film or a thin panel of mineral-filled plastic obtains a synergistically increased light barrier if light-absorbing particles of carbon black are added to it. By experiments, it has namely been possible to confirm that the inherent light barrier properties of the mineral-filled plastic film, which per se are insufficient to prevent undesired transmission of ultra violet rays, are considerably improved by an addition of but a very slight quantity of carbon black, which in turn entails only a slight blackening in comparison with the prior art technology. Visually, this may be expressed such that the interjacent layer in the packaging material according to the present invention will only be coloured grey, while the interjacent layer in the prior art packaging material is totally black.

The mechanism behind the synergistic light barrier effect which is surprisingly attained using the present invention has not been totally clarified, but could possibly be explained by the fact that the light-reflecting mineral particles extend the ray paths of the impinging light in the interjacent layer because of reflection against the particles, and that the probability that the light would collide with and be absorbed by the light-absorbing particles thereby increases. However, this explanation should not be seen as the only conceivable one, but is rather to be considered as a working hypothesis for describing the present invention.

The material in the mineral-filled interjacent layer comprises a plastic compound and particles embedded in the compound consisting, on the one hand, of a light-reflecting material and, on the other hand, a light-absorbing material.

The actual basic compound may consist of any suitable plastic whatever, such as polyolefin, polyester, polyamide etc., but is preferably a

polyolefin plastic which is already employed in commercial packages of bottle type.

Examples of such polyolefin plastics are polyethylene, such as high density polyethylene (HDPE), and polypropylene (PP) of both homo- and copolymer type, such as a copolymer of ethylene and propylene with a melt index between 0.5 and 5 according to ASTM (2.16 kg; 230°C) which is an already well-known and well-established copolymer in packaging contexts.

As the light-reflecting mineral filling in the interjacent layer, use may be made of any suitable particles whatever of montmorillonite, dolomite, calciumcarbonate, chalk, talcum, mica, clay etc., but use is preferably made of particles of dolomite, which is both readily available and moreover approved for use in packages for foods.

One example of a mineral-filled plastic compound for the interjacent layer in the packaging material according to the present invention is that which is described in, for example, EP O 353 991, EP O 353 498, EP O 494 594, EP O 494 0595, EP O 512 364, EP (94105439.7), EP (95926568.7) or EP (96935679.9). According to these specifications, the mineral-filled plastic compound preferably includes a copolymer of ethylene and propylene with a melt index between 0.5 and 5 according to ASTM (2.16 kg; 230°C) and particles of chalk admixed in the plastic compound in a quantity of between 50 and 80% of the total weight of the mineral-filled compound.

As light-absorbing material in the interjacent layer in the packaging material according to the present invention, use is made, as has already been mentioned, of particles of carbon black which, already in very small quantities, gives a synergistic effect in combination with the above-described mineral-filled plastic compound. In order to attain the desired light barrier, as small quantities as 0.04-1% of the total weight of the interjacent layer are sufficient, which effectively prevents the transmission of light, in particular ultra violet light, at the same time as the particles discolour (blacken) the interjacent layer to only an insignificant degree.

In one preferred embodiment of the packaging material according to the present invention, the interjacent layer thus consists of a polyolefine plastic compound containing between 3 and 80% filler particles, such as montmorillonite, dolomite, CaCO_3 , talcum, mica, clay etc. and between 0.04 and 1% light-absorbing particles of carbon black.

The outer plastic layer(s) in the packaging material according to the present invention can, but need not, consist of the same plastic compound as that of the interjacent layer. However, use is preferably made of the same plastic compound in all layers included in the material, since such a homogeneous material enjoys major advantages compared with a corresponding heterogeneous material in which different plastic compounds are employed.

A homogeneous material with the same plastic compound in all layers of the material can readily be produced by a conventional extrusion process using existing process equipment and requires no binders (adhesives) or other agents for permanently uniting the co-extruded material layers to one another.

BRIEF DESCRIPTION OF THE ACCOMPANYING DRAWING

The present invention will now be described in greater detail hereinbelow, with reference to the accompanying Drawing in which:

The Figure shows a schematic cross section of a particularly preferred packaging material for a package of bottle type according to the present invention.

DESCRIPTION OF PREFERRED EMBODIMENT

The packaging material carrying the generic reference numeral 10 in the Figure is of a triple layer structure consisting of an interjacent layer 11 and outer layers 12 and 13 on both sides of the interjacent layer 11.

The interjacent layer 11 consists of a plastic compound 11a and, substantially uniformly distributed in the compound, mineral filler particles 11b (unfilled squares in the Figure) and particles 11c of carbon black (black points in the Figure) which are preferably randomly distributed in the compound 11a between the mineral particles 11b.

The compound 11a in the interjacent layer 11 may, as has been mentioned previously, consist of basically any type whatever of plastic occurring in packaging contexts, but is preferably a plastic of the polyolefin type.

The mineral particles 11b in the interjacent layer 11 may also be any suitable type of particle whatever, e.g. montmorillonite, dolomite, calcium carbonate, talcum, mica, volastonite, clay etc., but in the illustrated example

consist of dolomite which already occurs in known packaging materials together with a polyolefine plastic as described in the immediately preceding paragraph.

5 The quantity mineral particles may vary within a very broad range from approx 3 and up to approx. 80% of the total weight of the compound. Preferably, the quantity of chalk in the interjacent layer 11 amounts to approx. 65% of the total weight of the compound. This preferred quantity imparts to the interjacent layer 11 good rigidity and thereby makes for the production of configurationally stable, easily handled bottles from the
10 packaging material 10 according to the present invention.

As was mentioned previously, an interjacent layer of plastic compound and mineral particles distributed in the compound per se possesses a certain light barrier property which, granted, is insufficient to wholly prevent the transmission of light, in particular ultra violet light, but
15 which is utilised most advantageously according to the present invention in order to attain the desired total barrier principally against the ultra violet light.

For the above-mentioned purpose, the interjacent layer 11 thus includes light-absorbing particles 11c of carbon black which, together with
20 the simultaneously present mineral particles 11b, has a synergistically elevating light barrier effect and which, even in very small quantities realises an efficient barrier for totally preventing the transmission of ultra violet light through the interjacent layer 11.

The quantity of carbon black in the interjacent layer 11 lies generally
25 within the range of 0.04-1% of the total weight of the interjacent layer, which is sufficiently large to attain the above-mentioned synergy effect, but at the same time sufficiently small so as not to overly blacken the interjacent layer.

The two outer layers 12, 13 on both sides of the interjacent layer 11 comprise, like the interjacent layer 11, a compound of plastic which in
30 principle may be any plastic whatever occurring in packaging contexts. Furthermore, the outer layers 12 and 13 may have mutually different compounds, but preferably have compounds of the same plastic which, more preferably still, is the same plastic as the plastic in the interjacent layer 11. In the illustrated embodiment, the two outer layers 12, 13 thus each
35 comprise a compound of a polyolefine plastic, such as a high density

polyethylene and copolymer of ethylene and propylene with a melt index between 0.5 and 5 according to ASTM (2.16 kg; 230°C).

Since the light-absorbing carbon black particles 11c in the interjacent layer 11 give the interjacent layer a certain grey tone which may be visible through the two outer layers 12 and 13, it may be appropriate (and in certain cases desirable) to conceal the interjacent layer 11 as far as is possible. To this end, white pigment is therefore suitably incorporated in at least that layer which is to form the outside of a package or bottle produced from the packaging material 10. Preferably, white pigment is incorporated in the interjacent layer as well. An advantageous white pigment is titanium dioxide (TiO₂).

Since the quantity of carbon black in the interjacent layer 11 is very small and the interjacent layer 11 will, as a result, be only slightly blackened, it will therefore be sufficient to employ very slight quantities of white pigment (TiO₂) in the one or both outer layers 12, 13 in order to conceal the interjacent layer 11. Suitable quantities of white pigment may vary up to approx. 5% of the total weight of the outer layer and of the interjacent layer, respectively, depending upon the pertinent quantity of carbon black in the interjacent layer 11.

A bottle produced from the above-described packaging material 10 may be produced by a combined extrusion and blow moulding operation. This production technique is well-known to a person skilled in the art and is described, for example, in published Swedish Patent Application No. 9503537-4 which, in relevant parts, is hereby included as a reference. For further details concerning this production technique, reference is therefore made to the above Swedish Patent Application.

Bottles produced from the packaging material 10 according to the present invention using the above-described method, by combined extrusion and blow moulding, may advantageously be employed for light-sensitive products in general, but have proved to be particularly advantageous in connection with so-called UHT milk, which may be stored for lengthy periods of up to several weeks in the bottles without being damaged as a result of the effects of light. Moreover, the bottles are light in weight and easy to handle, at the same time as displaying a consumer-attractive white appearance, despite the presence of carbon black in the packaging material.

It will thus have been apparent from the foregoing description that the present invention, with but very simple means, attains its object, at the same time as making possible the production of a packaging material and packages, respectively, with lower material consumption and therefore
5 lower material costs than those involved in the prior art technology.

While the packaging material and packages of bottle type produced from the packaging material have been described with particular reference to the illustrated embodiment shown in the Drawing, the present invention is, however, not restricted exclusively to this embodiment. It will be obvious
10 to a person skilled in the art that a number of different alterations and modifications of individual details are possible and self-evident without, to that end, departing from the inventive concept as this is defined in the appended Claims.

WHAT IS CLAIMED IS:


1. A packaging material of single or multi-layer type including at least one layer (11) of plastic which, for light barrier elevating purposes,
5 includes particles (11c) of carbon black, **characterized in that** the layer (11) containing carbon black also includes mineral particles (11b) substantially uniformly distributed in the compound (11a) of the layer.
2. The packaging material as claimed in Claim 1, **characterized in**
10 **that** the quantity of mineral particles (11b) in the layer (11) is between approx. 3 and 80% of the total weight of the layer.
3. The packaging material as claimed in Claim 1 or 2, **characterized in**
15 **that** the compound (11a) in the mineral-filled layer (11) containing carbon black consists of a plastic of polyolefin type.
4. The packaging material as claimed in any of the preceding Claims, **characterized in that** the compound (11a) in the mineral-filled layer (11) containing carbon black consists of a hig density polyethylene or a
20 copolymer of ethylene and propylene with a melt index between 0.5 and 5 according to ASTM (2.16 kg; 230°C).
5. The packaging material as claimed in Claim 4, **characterized in**
25 **that** the quantity of carbon black in the mineral-filled layer (11) is between 0.04 and 1% of the total weight of the compound (11a).
6. The packaging material as claimed in any of the preceding Claims, **characterized in that** the mineral-filled layer (11) containing carbon black is surrounded by outer layers (12 and 13) of plastic on both sides of the layer
30 (11), said outer layers (12 and 13) being permanently united to the layer (11) without interjacent binder or adhesive.
7. The packaging material as claimed in Claim 6, **characterized in**
35 **that** the two outer layers (12 and 13) consist of the same plastic as the plastic in the interjacent layer (11).

8. The packaging material as claimed in any of Claims 6 to 7, **characterized in that** of the two outer plastic layers (12 and 13) one includes a white pigment or other white colouring agent so as to conceal the interjacent layer (11) containing carbon black, at least from one direction.

5

9. A package, preferably a bottle, for light-sensitive products, **characterized in that** it is produced by a combined extrusion and blow moulding operation of a packaging material as claimed in any of Claims 1 to 8.

1/1



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00843

A. CLASSIFICATION OF SUBJECT MATTER

IPC6: B32B 27/20, B65D 65/20

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC6: B32B, B65D, C08K, C08L

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	JP 4173134 A (DAINIPPON PRINTING CO LTD) 1992-06-19 (abstract) World Patents Index (online). U.K.: Derwent Publications, Ltd. (retrieved on 1999-08-27). Retrieved from: EPO WPI database. DW9231, Accession no. 92-255458	1
Y	--	2-11
Y	EP 0353496 A1 (TETRA PAK FINANCE & TRADING S.A.), 7 February 1990 (07.02.90), abstract --	2-11

☒ Further documents are listed in the continuation of Box C.☒ See patent family annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art

"&" document member of the same patent family

Date of the actual completion of the international search

27 August 1999

Date of mailing of the international search report

01 -09- 1999

Name and mailing address of the ISA/

Swedish Patent Office

Box 5055, S-102 42 STOCKHOLM

Facsimile No. +46 8 666 02 86

Authorized officer

Jack Hedlund/Els

Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 99/00843

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	<p>File WPI, Derwent accession no. 94-196825, Dainippon Printing Co Ltd: "Container for liq.foods - includes paper layer, polyolefin- based resin layer on outside of paper layer, barrier layer of inorganic oxide thin film on inside, inner sealing layer and a light- shading;" & JP,A,6135439, 940517</p> <p>-- -----</p>	1-11

INTERNATIONAL SEARCH REPORT

Information on patent family members

02/08/99

International application No.

PCT/SE 99/00843

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 0353496 A1	07/02/90	SE 0353496 T3	
		AT 119830 T	15/04/95
		AU 614653 B	05/09/91
		AU 3914689 A	01/02/90
		CA 1333879 A	10/01/95
		CN 1018259 B	16/09/92
		CN 1039771 A	21/02/90
		CS 8904589 A	15/04/92
		CZ 283265 B	18/02/98
		DD 283970 A	31/10/90
		DE 68921678 D,T	27/07/95
		EP 0640461 A	01/03/95
		ES 2069552 T	16/05/95
		HU 210360 B	28/04/95
		JP 2175141 A	06/07/90
		JP 2848635 B	20/01/99
		KR 9409014 B	29/09/94
		LT 2596 A,R	25/03/94
		LT 126693 R	25/03/94
		LV 5612 A	10/05/94
		PT 91340 A,B	08/03/90
		RO 104653 A	25/04/93
		SE 467926 B,C	05/10/92
		SE 8802777 A	02/02/90
		SK 278374 B	05/02/97
		SU 1804430 A	23/03/93
		US 5143764 A	01/09/92
		US 5223194 A	29/06/93
		YU 150989 A	30/06/91
		SE 467917 B,C	05/10/92
		SE 8802778 A	02/02/90